





| Product Code | FLP-CHR-5177BPM |
|--------------------------------------|--|
| Description | Mono Sink Mixer with Pull-out Handspray & 375mm Long Braided Hoses |
| Connection Size | Braided hoses, 1/2" FIP (WRAS Approved) |
| | Withstand pressure of 10 Bar |
| Flow Rate | 13.52 LPM @ 3 bar |
| Recommended Water | 0.5 Bar - 5 Bar |
| Pressure | |
| Brass Specification in Percentage | Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) Brass Pipe as per IS:407-1996 Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder) |
| Cartridge Specification | NSF-61 Approved Cartridge with Temperature Limiter Cartridge with Brass Spindle Life Cycle EN 817: 70,000 cycles (Standard) - 2.1 LAC Cycles as per EN 817* - 10.5 LAC Cycles (ON/OFF)* |
| Water Tightness | 16 bar (Pass) |
| Pressure Resistance | 25 bar (Pass) |
| Finish | Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass) |
| Available Colour Finishing | Black Chrome (BCH) & Black Matt (BLM) |
| * As nor in-house testing | done on automatic life cycle testing machine made by Giussani, Italy |

^{*} As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.